

Beteckning/Reference

TSV 2016-960

Swedish Transport Agency



Communication concerning approval of a type of side-marker lamp marked SM1 pursuant to Regulation No 91

	Approval No	00008
1.	Trade name or mark of the side- marker lamp:	LED lamp L52, SM1
2.	Manufacturer's name for the type of side-marker lamp:	Standby AB
3.	Manufacturer's name and address	Standby AB Nohabgatan 12C 461 53 TROLLHÄTTAN
4.	If applicable, name and address of the manufacturer's representative	-
5.	Submitted for approval on	2016-06-21
6.	Technical service responsible for conducting approval tests	SP Technical Research Institute of Sweden Box 857 SE-501 15 BORÅS
7.	Date of report issued by that service	2016-09-15
8.	Number of report issued by that service	MTt6P05631-1rev1
9.	Concise description	
	Colour of light emitted:	Amber
	Number and category(ies) of light source(s):	6 LED amber, clear lens, SM1
	Light source module:	No
	Light source module specific identification code:	
	Only for limited mounting height equal to or less than 750 mm above the ground:	No
	Geometrical conditions of installation and relating variations, if any:	



Beteckning/Reference

TSV 2016-960

Swedish Transport Agency	у	137 2010-900
Application of source control g intensity control	-	
(a) Being part of	of the lamp:	N/A
(b) Being not p	art of the lamp:	N/A
electronic light) supplied by an source control ntensity control:	N/A
gear/variable in manufacturer a number (when control gear is	t source control ntensity control nd identification the light source part of the lamp but is to the lamp body):	N/A
10. Position of the	approval mark	See document X452 8 8XXXA
11. Reason for exte	ension (if applicable)	-
12. Approval		Granted
13. Place		Borlänge
14. Date	OSHAPPROVAL AUTHON	2016-11-18
.5. Signature	TRANSPORT STYRELSEN	Swedish Transport Agency Jangland Lars Rask

- 16. The list of documents deposited with the Administrative Service which has granted approval is annexed to this communication and may be obtained on request.
 - Technical information dated 2016-09-12, 1 page.
 - Test report, MTt6P05631-1rev1, 6 pages.