

Strølux

LED Work Light Bar

The Strølux range of LED work light bars combine the latest optical technology with market leading 5W Osram LEDs to provide excellent, additional working light in a variety of lengths to suit your application.

- Single or double row of LEDs
- Ultra bright 5W Osram LEDs
- From 6-96 LEDs per work light
- From a minimum of 1283 to a maximum of 16800 effective lumens
- Available in 6 lengths for each style
- Combination of flood and spot beams
- IP67 and IP69K ingress protected
- Supplied with adjustable bracket and fixings
- 12/24v operation
- ECE R10 (e) approved
- 2 year warranty

R10

IP67

IP69K

2YR
Warranty

SINGLE ROW

Part Number	Length	Number of LEDs	Effective Lumen	Dimensions (mm)	Max Current @12V
LSW-06WXC3-1	7" (177mm)	6	1283	177 (L) x 40 (H) x 54 (D)	2.1A
LSW-09WXC3-1	10" (246mm)	9	2054	246 (L) x 40 (H) x 54 (D)	3.4A
LSW-21WXC3-1	21" (522mm)	21	4652	522 (L) x 40 (H) x 54 (D)	8.0A
LSW-33WXC3-1	31" (798mm)	33	7445	798 (L) x 40 (H) x 54 (D)	12.5A
LSW-42WXC3-1	40" (1005mm)	42	9499	1005 (L) x 40 (H) x 54 (D)	14.9A
LSW-54WXC3-1	50" (1281mm)	54	12324	1281 (L) x 40 (H) x 54 (D)	19.2A

DOUBLE ROW

Part Number	Length	Number of LEDs	Effective Lumen	Dimensions (mm)	Max Current @12V
LSW-12WXC3-2	8" (204mm)	12	2100	204 (L) x 70 (H) x 67 (D)	3.8A
LSW-24WXC3-2	14" (357mm)	24	4200	357 (L) x 70 (H) x 67 (D)	7.7A
LSW-40WXC3-2	22" (561mm)	40	7000	561 (L) x 70 (H) x 67 (D)	14.6A
LSW-60WXC3-2	32" (815mm)	60	10500	815 (L) x 70 (H) x 67 (D)	20.8A
LSW-80WXC3-2	42" (1076mm)	80	14000	1067 (L) x 70 (H) x 67 (D)	28.3A
LSW-96WXC3-2	50" (1274mm)	96	16800	1274 (L) x 70 (H) x 67 (D)	30.6A



STRØLUX

