Mini Stealth

12~24VDC

6+6 LED DUAL COLOUR LIGHTHEAD

(Surface Mount/ Hood Mount)









- 6LED+6LED Dual colour.
- SAE Class 1 high power output.
- ECE R10 EMC Compliance.
- 0.68" (17.2mm) low-profile thickness.
- Long life LEDs rated to 100,000 hours of operation.
- Non-volatile memory recalls last flash pattern used at power up.
- Multi-units synchronization in simultaneous or alternating flash.
- Reverse polarity protection.
- Weatherproof and vibration resistant design for internal or external use.
- Aluminium base for efficient heat dissipation.

SPECIFICATIONS

Compliance: SAE J595, CA13 (R/B/Y), ECE R10-04

LED Elements: High-power LED x 12pcs

No. of Warning Patterns: 16 or 26 Flash Patterns

(depend on model)

Operating Voltage: 12~24VDC

Avg. Current: 0.6A@12VDC / 0.3A@24VDC **Max. Current:** 1.2A@12VDC / 0.6A@24VDC

Avg. Power: 7.2W Max. Power: 14.4W

Wires: Red-Vcc: 20cm (20AWG)

Black-GND: 20cm (20AWG)

Yellow-Flash Patterns & Sync: 20cm (20AWG)

White-Vcc: 20cm (20AWG)

Synchronization: 15 units


Fuse Rating: 2A

Storage Temp. (°C): -40°C to +75°C Working Temp. (°C): -30°C to +65°C LED Colour: Red, Blue, Amber, White


Lens Colour: Clear Warranty: 5 Years

DIMENSIONS

SURFACE MOUNT



HOOD MOUNT



PART NO.

- M056-0x13y-00R
- M056-0x23y-00R

Replace x for Mounting:

0 = Surface Mount 1 = Hood Mount

Replace y for Colour:

FLASH PATTERN

FLASH PATTERNS			
1	Double [R65]	14	Single-Quad
2	Single [2Hz]	15	Single H/L
3	Triple [2Hz]	16	Singe-Triple-Quint
4	Quad [2Hz]	17	Single-Single
5	Random		Double-Double
6	Steady	19	Triple-Triple Fast
7	Single [SAE][CA	13] 20	Triple-Triple Mid
8	Mega	21	Quint-Triple
9	Double [SAE]	22	7-1 Flash
10	Triple [SAE]	23	1-7 Flash
11	Quad [SAE]	24	Quad-Single
12	Quin [SAE]	25	Single-Quad
13	Ultra [SAE]	26	Quint-Quint

^{*}FP# 17~26 are only available in dual colour flashing mode.